

RF Antenna Assembly

Specification (單天線)

1. Electrical Properties :


- 1.1 Frequency Range.....3.4GHZ~3.8GHZ
- 1.2 Impedance 50Ω Nominal
- 1.3 VSWR2.1 : 1 Max.
- 1.4 Return Loss.....-8.99 dB Max.
- 1.5 RadiationOmni-directional
- 1.6 Gain(peak).....5dBi (單天線) (with cable loss)
- 1.7 Polarization.....Linear; Vertical
- 1.8 Admitted Power..... 1W
- 1.9 Cable.....RG-178 Coaxial Cable
- 1.10 Connector.....SMA

2. Physical Properties :


- 2.1 Antenna Cover.....ABS
- 2.2 Antenna Base..... PC
- 2.3 Antenna Base..... PC+PBT
- 2.4 Operating Temp.-10℃ ~ +60℃
- 2.5 Storage Temp.-10℃ ~ +70℃
- 2.6 ColorBlack

CG-


REV	DATE	DESCRIPTION
X1	05/05-2015	New Issue
X2	05/26-2015	Modify Package



GP標籤貼於外箱兩邊側麥左上角



Packing : 2pcs/bag



6	Connector	BIG SMA Straight Plug Standard	1	
5	Cable	RG-178 Cable	1	
4	Rivet	POM,Color: Black	2	
3	Antenna Base	(CD-13)PC+PBT; Color : Black	1	
2	Antenna Base	(CD-761)PC ; Color : Black	1	
1	Antenna Cap	(CD-702)ABS ; Color : Black	1	
NO	DESCRIPTION		Q'TY	REMARK

XX.	±5.0	APPROVED	羅家鎮
X.	±3.0	2015.5.5	
.X	±1.0	CHECKED	林凱元
.XX	±0.5	2015.5.5	
.XXX	±0.1	DRAWING	徐筱惠
		2015.5.5	

CUSTOMER:		
PART NO :	11320Y20TD0ZYG1D1	
PART NAME:	RF Antenna Assembly	
W.Y P/NO :	C381-510254-A	
REV	UNIT	FILE : SRF2015832
X2	mm	SHEET : 1/1

M.gear Wha Yu Group

THIS DRAWING, AND IT'S INHERANT DESIGN CONCEPTS, ARE THE PROPERTY OF WHA YU AND AS SUCH MAY NOT BE COPIED, REPRODUCED, OR GIVEN TO THIRD PARTIES WITHOUT THE WRITTEN CONSENT OF WHA YU.

CUSTOMER'S SINGATURE

Antenna Test Report

For

NE3-15018

V1.00

Document Number	NE3-15018
1st Released Date	03/27/15
Last Released Date	03/27/15
Author	Stone
Review by	SKY


Revised History

[illegible]

Specification


Rough description		
Item	Initial Specification	Final Specification
Dimensions	NA	
Impedance	50Ω	
Test environment	With Housing	
Application	None	
Freq. Range	3.4GHz~3.8GHz	
Antenna type	DIPOLE	
GAIN	ANT1 (5dBi)	
VSWR	2.1:1	
Radiation	None	
Polarization	Linear	
HPBW / H	None	
HPBW / E	None	
Connector type	SMA	
Cable type	RG-178	

1 Antenna Introduction





2 S11 test results

4.1 ANT 1.




3 Gain & Patterns test results

3.1 Measurement setting




	XY	YZ	XZ
0°	Right	Up	Up
90°	Back	Back	Right
180°	Left	Down	Down
270°	Front	Front	Left



	θ	ϕ
Total angle	175°	360°
How many angle scan one point	5°	5°
Total scan point	36	73


3.2 ANT 1.

3400 MHz~3800 MHz




X-Z Plane (E-total)

3400 MHz~3800 MHz



Y-Z Plane (E-total)

3400 MHz~3800 MHz



X-Y Plane (E-total)

4.0 Return Loss

Frequency	Ant 1. (dB)
3400MHz	-21.63
3500MHz	-38.71
3600MHz	-24.93
3700MHz	-19.38
3800MHz	-14.28

4.1 3D total Peak Gain & Efficiency

Frequency	Ant 1.	
	Peak Gain (dBi)	Efficiency (%)
3400MHz	5.01	71.30
3500MHz	5.08	71.45
3600MHz	5.12	71.46
3700MHz	5.15	71.50
3800MHz	4.88	71.15